



General Purpose Corded Handheld Contact Linear Imager Bar Code Reader

The Touch 65/95 linear imaging contact readers are an excellent value for those seeking a cost-effective solution for general purpose document handling and retail applications

Touch 65/90™ Pro provides a complete all in one multi-interface solution, including RS-232, USB, Wedge and Wand Emulation while Touch 65/90 Light provides USB or PS2 Wedge and RS-232 single models. Both feature high first pass read rates by combining excellent reading performance with advanced code reconstruction for reading damaged or poorly printed codes, resulting in higher productivity. Data editing and data formatting modes are available to format the collected data as required by the application software.

The Touch readers are available with 65 mm / 2.6 in and 90 mm / 3.5 in reading windows, for reading standard and wider bar codes.

The Touch readers are available in triggered models. They can also be used as triggerless readers, by simply disabling the trigger with a configuration command.

Available in Dark Grey, additional custom color options are available for a minimum order quantity.



Features

- Wide reading windows: 65 mm / 2.6 in and 90 mm / 3.5 in
- Accurate and high first-pass read rates with enhanced label reconstruction for damaged or poorly printed codes
- Advanced data formatting and editing (65/90 Pro)
- Multi-interface USB, RS-232, Wedge and Wand Emulation (65/90 Pro)
- Supports GS1 DataBar™ linear codes

Specifications

DECODING CAPABILITY

1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 Databar™ linear codes

ELECTRICAL

CURRENT

Operating (Typical): 100 mA @ 5 VDC
Standby/Idle (Typical): < 500 µA @ 5 VDC

INPUT VOLTAGE

5 VDC +/- 5%

ENVIRONMENTAL

AMBIENT LIGHT

0 - 2,000 lux

DROP RESISTANCE

Withstands repeated drops from 1.2 m / 3.9 ft onto a concrete surface

ESD PROTECTION (AIR DISCHARGE)

16 kV

HUMIDITY (NON-CONDENSING)

90%

PARTICULATE AND WATER SEALING

IP30

TEMPERATURE

Operating: 0 to 55 °C / 32 to 131 °F
Storage/Transport: -20 to 70 °C / -4 to 158 °F

INTERFACES

Keyboard Wedge: 65/90 Light; RS-232 / USB / Keyboard Wedge / Wand Multi-Interface: 65/90 Pro; USB: 65/90 Light; Wand: 65/90 Light

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE

Dark Grey; Other colors and custom logo options are available for minimum quantity purchase.

DIMENSIONS

Touch 65: 16.4 x 7.8 x 6.3 cm / 6.5 x 3.0 x 2.5 in
Touch 90: 17.5 x 10.0 x 8.0 cm / 6.9 x 3.9 x 3.1 in

WEIGHT

Touch 65: 160.0 g / 5.6 oz
Touch 90: 195.0 g / 6.9 oz

READING PERFORMANCE

IMAGER SENSOR

CCD Solid-state 2048 pixels

PRINT CONTRAST RATIO (MINIMUM)

Light Models: 25%

Pro Models: 15%

256 reads/sec.

READ RATE (MAXIMUM)

Beeper (Adjustable Tone); Good Read LED

READING INDICATORS

Touch 65: 0.100 mm / 4 mils

RESOLUTION (MAXIMUM)

Touch 90: 0.130 mm / 5 mils

READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

5 mils: 0 to 2.5 cm / 0 to 1.0 in

7.5 mils: 0 to 4.3 cm / 0 to 1.7 in

10 mils: 0 to 5.0 cm / 0 to 2.0 in

13 mils: 0 to 6.8 cm / 0 to 2.7 in

20 mils: 0 to 8.0 cm / 0 to 3.2 in

SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

The Quick Reference Guide for this product can be referred to for a complete list of certifications.

ENVIRONMENTAL COMPLIANCE

Complies to China RoHS; Complies to EU RoHS

UTILITIES

DATALOGIC ALADDIN™

Datalogic Aladdin configuration program is available for download at no charge

OPOS / JAVAPOS

JavaPOS Utilities are available for download at no charge

OPOS Utilities are available for download at no charge

WARRANTY

5-Year Factory Warranty



Mounts/Stands

- 90ACC1878 Desk/Wall Holder for Touch 65 (SPC-TOUCH65)
- 90ACC1879 Desk Holder for Touch 65/90 (SPC-TOUCH65/90)

© 2007-2008 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws.
• Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo, Datalogic Aladdin, PuzzleSolver and Touch are trademarks of Datalogic S.p.A.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-TOUCH-ENA4 20080916

www.scanning.datalogic.com